



PrintBox 9000

Mobile and Desktop Printing over Wi-Fi, Network, Cloud or USB for Labels, Ticketing and Receipts



Model

PrintBox 9000

Standard Ports

Ethernet, (4) USB 2.0

Keys

Not Required

SQL Database Support

Standard

Housing

Network-connected

USB 2.0 Ports

4

Printer Compatibility

ZPL or ESC/POS as Standard, others by request

Programming & Designing Templates

Web-Enabled or USB Stick Updates for standard ZPL or ESC/POS Templates. Multiple template design options available - PC applications or custom build

PRINTBOX 9000

- Desktop and Mobile printing can be accessed from the same PrintBox by using ANY device with a web browser: PC, RFID terminal, smartphone or tablet.
- A Wi-Fi or network infrastructure is not always necessary as PrintBox can generate its own connectivity. For maximum connectivity flexibility the PrintBox also supports Bluetooth.
- Android "on-device" version of APPiWORX for mobile, desktop, hospitality and retail label printing in a standalone or multi-mode Mobile Printing environment coming soon.
- SQL database management standard.

PrintPad 900 Series With Alphanumeric Keyboard

If an alphanumeric keypad is required with PrintBox 9000 functionality, see the CloudBox 900 Series.

APPiWORX

Recognizing the need to create custom label formats without having write application software, APPiWORX is an easy to use embedded label design application on the PrintBox 970 and PrintPad 9000. For mobile capability in a standalone environment, APPiWORX can run on an Android terminal using a Bluetooth or Wi-Fi mobile printer.



CloudBox Inc.

Specifications

Design Fully enclosed Linux-based solution containing hardware and software tailored to print standard or custom labels, receipts and/or tickets via any smart device with a browser to access the print options available.

Warranty 12 months RTB

Physical

Enclosure Mold Black ABS: Terluran
Enclosure Color Black
Operating Temperature 14°F ±122°F
 -10°C ± 50°C
Operating Humidity 10% - 90% relative humidity
Power Consumption 500-800mA

Certifications

FCC, CE, RoHS

Power

6.5—32V Input

Dimensions

Length 118 mm / 4.6"
Height 53mm / 2.1"
Width 79 mm / 3"

Features

- Ethernet port connection
- Uses ZPL and ESC/POS commands. Others upon request
- Custom cables available to connect to a range of receipt and label printers.
- 4 * USB 2.0 Port.
- USB Ports for printer, scanner, scale or keyboard connections
- Works with a wide range of Printers – Direct or Networked
- Real Time Clock feature for time and date sensitive applications
- Runs on Linux OS
- Includes custom Command Set for flexible printing functionality
- Wi-Fi and Bluetooth connectivity
- Automatic label template updates over the network or from USB stick

